

Although we **SPECIALIZE IN CUSTOMIZATION**, we also have a standard cylindrical cell range.

Specifications of basic cylindrical cells:

Model	Nominal Voltage	Typical capacity	Internal impedance	Dimensions		Charge and discharge	
				Diameter	Height	Charge	Discharge
Units	V	mAh	mΩ	mm	mm	C	C
HUB14500	3.7	900	≤80	14	50	0.5-1	0.5-1
HUB17280	3.7	600	≤100	16.3	28	0.5-1	0.5-1
HUB17335	3.7	700	≤100	16.3	33.5	0.5-1	0.5-1
HUB18500	3.7	1400	≤70	18.1	50	0.5-1	0.5-1
HUB18650	3.7	2000	≤50	18.1	64.8	0.5-1	0.5-1
HUB18650	3.7	2000	≤40	18.1	65	0.5-1	3-5
HUB18650	3.7	2200	≤40	18.1	65	0.5-1	3-5
HUB18650	3.7	2600	≤70	18.1	64.8	0.5-1	0.5-1
HUB26650	3.7	3500	≤30	26	65.5	0.5-1	0.5-1
HUB26650	3.7	5000	≤30	26	65.5	0.5-1	0.5-1
HUB18650	3.7	1500	≤15	18.1	64.8	1	10-15
HUB26650	3.7	2200	≤15	26	64.8	1	10-15
HUB21700	3.7	4000	≤20	21	70	0.5-1	0.5-1
HUB14430	3.2	400	≤115	13.8	43	0.5-1	0.5-1
HUB14500	3.2	400	≤95	13.8	50.2	0.5-1	0.5-1
HUB14500	3.2	650	≤80	13.8	50.2	0.5-1	0.5-1
HUB18500	3.2	600	≤80	18	50	0.5-1	0.5-1
HUB18500	3.2	1200	≤80	18	64.8	0.5-1	0.5-1
HUB18650	3.2	1500	≤65	18	64.8	0.5-1	0.5-1
HUB18650	3.2	1700	≤80	18	65.3	0.5-1	0.5-1
HUB26650	3.2	3400	≤20	26	65.3	0.5-1	0.5-1
HUB18650	3.2	1100	≤20	18	65.3	1-3	10-25
HUB26650	3.2	2400	≤20	26	65.3	1-3	10-25
HUB32650	3.2	6000	≤20	32	65.3	0.5-1	0.5-1
HUB32700	3.2	6000	≤20	32	70	0.5-1	0.5-1