

Although we **SPECIALIZE IN CUSTOMIZATION**, we also have a standard pouch cell range.

Specifications of basic pouch cells:

No.	Nominal capacity	Minimal capacity	Internal impedance	Nominal Voltage	Dimensions		
					Thickness	Width	Height
Units	mAh	mAh	mΩ	V	mm	mm	mm
1	60	60	≤500	3.7	4.4	10.0	21.0
2	50	48	≤600	3.7	2.5	10.0	35.0
3	40	35	≤700	3.7	3.0	10.5	28.0
4	60	50	≤550	3.7	4.0	11.5	24.0
5	250	250	≤100	3.7	5.0	20.3	27.5
6	450	450	≤100	3.7	3.5	20.0	72.5
7	610	610	≤60	3.7	4.3	25.3	53.0
8	850	850	≤60	3.7	5.0	25.0	80.0
9	700	680	≤60	3.7	4.0	26.0	65.0
10	800	800	≤60	3.7	5.0	26.0	85.0
11	1200	1150	≤60	3.7	7.8	27.0	50.5
12	1400	1400	≤50	3.7	6.3	27.5	64.5
13	1000	1000	≤50	3.7	3.2	47.0	95.0
14	2300	2250	≤50	3.7	9.0	48.0	52.0
15	1650	1650	≤50	3.7	4.9	50.0	55.0
16	3000	3000	≤40	3.7	3.9	62.0	108.0
17	3300	3300	≤40	3.7	2.9	62.0	143.0
18	4000	4000	≤40	3.7	3.4	69.0	149.0
19	3000	3000	≤45	3.7	3.8	69.5	98.5
20	3400	3400	≤40	3.7	4.2	70.0	107.0
21	3500	3500	≤40	3.7	3.4	75.5	105.0
22	4500	4500	≤40	3.7	4.0	79.0	115.0
23	5000	5000	≤30	3.7	3.3	79.0	152.0
24	3800	3800	≤30	3.7	3.7	81.5	99.5
25	6100	6000	≤50	3.7	5.2	84.0	121.0
26	3800	3800	≤30	3.7	3.0	89.0	117.0
27	6600	6600	≤30	3.7	3.6	101.0	156.0
28	5000	5000	≤30	3.7	2.6	108.5	156.5
29	5800	5800	≤30	3.7	2.6	122.5	140.5