

Although we **SPECIALIZE IN CUSTOMIZATION**, we also have a standard prismatic cell range.

Specifications of basic prismatic cells:

Model No		HUBE- 40A32	HUBE- 50A2V32	HUBE- 50A3V32	HUBE- 200A32V	HUBE- 275A32V
Typical Capacity (Ah) @0.2C		40	50	50	200	275
Nominal Voltage (V)		3.2	3.2	3.2	3.2	3.2
Dimension - LxBxH (mm)		148x27x97	148x40x103	148x27x129	173x53x207	173x71x207
Weight (g)		0.86	1.15	0.86	4.1	5.2
Internal Resistance (mΩ)		1	1	1	0.2	0.4
Discharge		3C	3C	3C	3C	3C
Charge	Standard Charging Current	0.5C	0.5C	0.5C	0.5C	0.5C
	Maximum Charging Current	1C	1C	1C	1C	1C
	Cutoff Voltage (V)	3.6	3.6	3.6	3.6	3.6
Temperature	Operating	0~45°C	0~45°C	0~45°C	0~45°C	0~45°C
	Storage	-20~60°C	-20~60°C	-20~60°C	-20~60°C	-20~60°C
Life Cycles		2000 cycles	2000 cycles	2000 cycles	2000 cycles	2000 cycles

